

DAK2225**低频高压二极管**

反向电压: 25 kV 正向电流: 200 mA

Standard Recovery High Voltage Diode

Reverse Voltage: 25 kV

Average Forward Current: 200 mA

技术资料**Technical Data**

- 产品级别: 外贸级
- 封装形式: 环氧封装
- 引线: 轴向
- 极性: 色环指示负极
- Product Grade: International Standard
- Package Type: Epoxy Encapsulation
- Lead: Axial Lead
- Polarity: Cathode Indicated by Color Band

产品标准**Product Standard**

Q/FT TRV0003-2022 《高压二极管》

验收标准**Acceptance Criteria**

GB/T 4023-1997 《半导体器件分立器件和集成电路 第2部分: 整流二极管》

Semiconductor Devices-Discrete Devices and Integrated Circuits-Part 2: Rectifier Diodes

外形尺寸**External Dimensions**

封装代号: HVD-721; 详见右图

Package Code: HVD-721; Please refer to the figure on the right.





特性及参数值

Characteristics and Parameter

除非另有规定，环境温度均为 25°C。

The ambient temperature is 25°C unless otherwise specified.

电气特性 Electrical Characteristics	符 号 Symbol	额定值 Ratings	单 位 Unit
最大反向重复峰值电压 Maximum Repetitive Peak Reverse Voltage	V_{RRM}	25	kV
最大反向不重复峰值电压 Maximum Non-repetitive Peak Reverse Voltage	V_{RSM}	26	kV
最大正向平均电流 Maximum Average Forward Current (@ $T_{oil} = 55^{\circ}\text{C}$)	$I_{F(AV)}$	200	mA
最大正向浪涌电流 Maximum Forward Surge Current	I_{FSM}	20	A
最大正向峰值电压 Maximum Peak Forward Voltage (@ $I_F = I_{F(AV)}$)	V_{FM}	≤ 26	V
最大直流反向电流 Maximum DC Reverse Current (@ $V_R = V_{RRM}$)	I_R	≤ 2 ($T_a = 25^{\circ}\text{C}$)	μA
		≤ 10 ($T_{oil} = 100^{\circ}\text{C}$)	
有效工作结温 Operating Junction Temperature Range	T_J	$-55 \sim +125$	$^{\circ}\text{C}$
贮存温度 Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^{\circ}\text{C}$