

UAF5015**特高频高压二极管**

反向电压: 15 kV, 正向电流: 50 mA, 反向恢复时间: 50 ns

Ultra-Fast Recovery High Voltage Diode

Reverse Voltage: 15 kV

Average Forward Current: 50 mA

Maximum Reverse Recovery Time: 50 ns

技术资料**Technical Data**

- 产品级别: 外贸级
- 封装形式: 环氧封装
- 引线: 轴向
- 极性: 色环指示负极
- Product Grade: International Standard
- Package Type: Epoxy Encapsulation
- Lead: Axial Lead
- Polarity: Cathode Indicated by Color Band

产品标准**Product Standard**

Q/FT TRV0003-2022 《高压二极管》

验收标准**Acceptance Criteria**


GB/T 4023-1997 《半导体器件分立器件和集成电路 第2部分: 整流二极管》

Semiconductor Devices-Discrete Devices and Integrated Circuits-Part 2: Rectifier Diodes

外形尺寸**External Dimensions**

封装代号: HVD-415; 详见右图

Package Code: HVD-415; Please refer to the figure on the right.



单位: mm

HVD-415



特性及参数值

Characteristics and Parameter

除非另有规定，环境温度均为 25°C。

The ambient temperature is 25°C unless otherwise specified.

电气特性 Electrical Characteristics	符 号 Symbol	额定值 Ratings	单 位 Unit
最大反向重复峰值电压 Maximum Repetitive Peak Reverse Voltage	V_{RRM}	15	kV
最大反向不重复峰值电压 Maximum Non-repetitive Peak Reverse Voltage	V_{RSM}	16	kV
最大正向平均电流 Maximum Average Forward Current (@ $T_{oil} = 55^{\circ}C$)	$I_{F(AV)}$	50	mA
最大正向浪涌电流 Maximum Forward Surge Current	I_{FSM}	5	A
最大正向峰值电压 Maximum Peak Forward Voltage (@ $I_F = I_{F(AV)}$)	V_{FM}	≤ 20	V
最大直流反向电流 Maximum DC Reverse Current (@ $V_R = V_{RRM}$)	I_R	$\leq 2 (T_a = 25^{\circ}C)$	μA
		$\leq 10 (T_{oil} = 100^{\circ}C)$	
最大反向恢复时间 Maximum Reverse Recovery Time ($I_F = 100mA$, $I_R = 200mA$)	t_{rr}	≤ 50	ns
有效工作结温 Operating Junction Temperature Range	T_J	$-55 \sim +125$	$^{\circ}C$
贮存温度 Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^{\circ}C$