

ADX8210**表面贴装 低频高压二极管**

反向电压：10 kV，正向电流：800 mA

Surface Mount Standard Recovery High Voltage Diode

Reverse Voltage 10 kV

Average Forward Current 800 mA

技术资料**Technical Data**

- 产品级别：外贸级
- 封装形式：环氧封装
- 引线：表面贴装内弯式
- 极性：色带指示负极
- Product Grade: International Standard
- Package Type: Epoxy Encapsulation
- Lead: Inside Bend
- Polarity: Cathode Indicated by Color Band


**产品标准****Product Standard**

Q/FT TRV0003-2022 《高压二极管》

外形尺寸**External Dimensions**

封装代号：HVS-607E

Package Code: HVS-607E

**HVS-607E**



验收标准

Acceptance Criteria

GB/T 4023 《半导体器件分立器件和集成电路 第2部分：整流二极管》

Semiconductor Devices-Discrete Devices and Integrated Circuits-Part 2: Rectifier Diodes

特性及参数值

Characteristics and Parameter

除非另有规定，环境温度均为 25°C。

The ambient temperature is 25°C unless otherwise specified.

电气特性 Electrical Characteristics	符 号 Symbol	额定值 Ratings	单 位 Unit
最大反向重复峰值电压 Maximum Repetitive Peak Reverse Voltage	V_{RRM}	10	kV
最大反向不重复峰值电压 Maximum Non-repetitive Peak Reverse Voltage	V_{RSM}	11	kV
最大正向平均电流 Maximum Average Forward Current (@ $T_{oil} = 55^{\circ}\text{C}$)	$I_{F(AV)}$	800	mA
最大正向浪涌电流 Maximum Surge Current	I_{FSM}	40	A
最大正向峰值电压 Maximum Peak Forward Voltage (@ $I_F = I_{F(AV)}$)	V_{FM}	≤ 11	V
最大直流反向电流 Maximum DA Reverse Current (@ $V_R = V_{RRM}$)	I_R	≤ 2 ($T_{oil} = 25^{\circ}\text{C}$)	μA
		≤ 20 ($T_{oil} = 100^{\circ}\text{C}$)	
有效工作结温 Operating Junction Temperature Range	T_J	$-55 \sim +125$	$^{\circ}\text{C}$
贮存温度 Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^{\circ}\text{C}$