

**DA623****表面贴装 低频高压二极管**

反向电压：3 kV，正向电流：600 mA

Surface Mount Standard Recovery High Voltage Diode

Reverse Voltage 3 kV

Average Forward Current 600 mA

**技术资料****Technical Data**

- 产品级别：外贸级
- 封装形式：环氧封装
- 引线：表面贴装内弯式
- 极性：色带指示负极
- Product Grade: International Standard
- Package Type: Epoxy Encapsulation
- Lead: Inside Bend
- Polarity: Cathode Indicated by Color Band



**产品标准****Product Standard**

Q/FT TRV0003-2022 《高压二极管》

**外形尺寸****External Dimensions**

封装代号：HVS-304E

Package Code: HVS-304E



单位：mm

**HVS-304E**



## 验收标准

## Acceptance Criteria

GB/T 4023 《半导体器件分立器件和集成电路 第2部分：整流二极管》

Semiconductor Devices-Discrete Devices and Integrated Circuits-Part 2: Rectifier Diodes

## 特性及参数值

## Characteristics and Parameter

除非另有规定，环境温度均为 25°C。

The ambient temperature is 25°C unless otherwise specified.

| 电气特性<br>Electrical Characteristics                                          | 符 号<br>Symbol | 额定值<br>Ratings                         | 单 位<br>Unit |
|-----------------------------------------------------------------------------|---------------|----------------------------------------|-------------|
| 最大反向重复峰值电压<br>Maximum Repetitive Peak Reverse Voltage                       | $V_{RRM}$     | 3                                      | kV          |
| 最大反向不重复峰值电压<br>Maximum Non-repetitive Peak Reverse Voltage                  | $V_{RSM}$     | 3.3                                    | kV          |
| 最大正向平均电流<br>Maximum Average Forward Current<br>(@ $T_{oil} = 55^{\circ}C$ ) | $I_{F(AV)}$   | 600                                    | mA          |
| 最大正向浪涌电流<br>Maximum Surge Current                                           | $I_{FSM}$     | 15                                     | A           |
| 最大正向峰值电压<br>Maximum Peak Forward Voltage<br>(@ $I_F = I_{F(AV)}$ )          | $V_{FM}$      | $\leq 4$                               | V           |
| 最大直流反向电流<br>Maximum DA Reverse Current<br>(@ $V_R = V_{RRM}$ )              | $I_R$         | $\leq 2$ ( $T_{oil} = 25^{\circ}C$ )   | $\mu A$     |
|                                                                             |               | $\leq 10$ ( $T_{oil} = 100^{\circ}C$ ) |             |
| 有效工作结温<br>Operating Junction Temperature Range                              | $T_J$         | $-55 \sim +125$                        | $^{\circ}C$ |
| 贮存温度<br>Storage Temperature Range                                           | $T_{STG}$     | $-55 \sim +150$                        | $^{\circ}C$ |